

# OMNIKEY® 5321 CL USB Reader



## CONTACTLESS USB SMART CARD READER

- **Versatile Applications** – Ideal for end-user environments with different contactless smart card technologies and tags in use
- **Fast Contactless Transmission** – Supports contactless smart cards up to 848 Kbps in fastest ISO 14443 A/B
- **Designed for User Convenience** – Housing design is optimized for advanced contactless applications
- **Readily compliant** – Supports HID® iCLASS® and MIFARE® as well as ISO 14443A/B and ISO 15693

Housed in a robust closed housing with a convenient card retainer, the OMNIKEY® 5321 CL represents the ideal reader for contactless technology applications. Featuring a PC-linked reader that reads/writes to 13.56 MHz contactless smart cards in all three HF standards, the OMNIKEY 5321 CL economically supports end-user environments where a variety of contactless cards and tags are used.

- Supports three ISO standards for contactless cards (ISO 14443 A/B and 15693) and Microsoft WHQL
- Reader supports contactless smart cards with up to 848 Kbps in the fastest ISO 14443 transmission mode
- Standard application interfaces include PC/SC, Synchronous-API (on top of PC/SC), OCF (Open Card Framework) or CT-API

For actual driver downloads please visit [hidglobal.com/omnikey](http://hidglobal.com/omnikey)

**CONTACTLESS TECHNOLOGIES SUPPORTED:**

- HID: iCLASS®
- NXP: MIFARE®, DESFire®, SMART-MX and ICODE
- Texas Instruments: TagIT®
- ST Micro: x-ident, SR 176, SR 1X 4K
- Infineon: My-d (in secure mode UID only)
- Atmel: AT088RF020
- KSW MicroTech: KSW TempSens
- iCODE SLI, iCODE SL2 & LRI 64
- Contactless 2048 bit key generation in RSA mode (JCOP / SMART-MX)

**SPECIFICATIONS**


<b>Model Name</b>	OMNIKEY® 5321
<b>Dimensions</b>	3.78" x 3.07" x .031" (115 x 96.5 x 25.5 mm)
<b>Weight</b>	Approx. 5.64 oz / 160 g
<b>Power Supply</b>	Bus powered
<b>Operating Temperature</b>	32°-131° F (0° - 55° C)
<b>Operating Humidity</b>	10-90% rH
<b>HOST INTERFACE</b>	
<b>Host Interface</b>	USB 2.0 (also compliant with USB 1.1)
<b>Transmission Speed</b>	12 Mbps (USB 2.0 full speed)
<b>CONTACTLESS SMART CARD INTERFACE</b>	
<b>Protocols</b>	T=CL, MIFARE®, iCLASS® / ISO 14443 A with 848 Kbps transmission rate (depending on card) / ISO 14443 B with 848 Kbps transmission rate (depending on card) / ISO 15693 with 26 Kbps transmission rate (depending on card)
<b>Supported APIs</b>	PC/SC driver (ready for 2.01), Synchronous API (on top of PC/SC)
<b>PC/SC Driver Support</b>	Windows® XP / Vista / Windows 7 / Windows 8, 2003 / 2008 Server, Windows® CE 5.0 / CE.NET / CE 6.0 (depending on hardware), Linux® and Mac® OS X
<b>Status Indicator</b>	Dual color LED (green=ready, red=busy)
<b>Reader Board</b>	Also available as PCB
<b>Color</b>	Dark grey
<b>Options</b>	Customer Specific Logo: Available upon request
<b>Composition</b>	ABS
<b>Connector Cable</b>	70.9" (180 cm)
<b>Meantime Between Failure (MTBF)</b>	500,000 hours
<b>Compliance/Certification</b>	Microsoft® WHQL <sup>1</sup> , USB 2.0 (USB 1.1 compatible), GSA FIPS 201 approved product list (in preparation)
<b>Safety/Environmental</b>	CE, FCC, UL, RoHS, WEEE
<b>Warranty</b>	Two year manufacturer's warranty. (For drivers, see complete lifetime support policy.)

<sup>1</sup> = Windows® Hardware Quality Lab



North America: +1 949 732 2000  
 Toll Free: 1 800 237 7769  
 Europe, Middle East, Africa: +44 1440 714 850  
 Asia Pacific: +852 3160 9800  
 Latin America: +52 55 5081 1650

[hidglobal.com](http://hidglobal.com)

**ASSA ABLOY**

An ASSA ABLOY Group brand

© 2013 HID Global Corporation/ASSA ABLOY AB. All rights reserved. HID, HID Global, the HID Blue Brick logo, the Chain Design, OMNIKEY and iCLASS are trademarks or registered trademarks of HID Global or its licensor(s)/supplier(s) in the US and other countries and may not be used without permission. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners.  
 2013-04-15-hid-ok-5321-cl-usb-readers-ds-en